



| Equipment Specifications *   |                                    |                   |                                   |
|------------------------------|------------------------------------|-------------------|-----------------------------------|
| Automatic Turndown           | 0-100% Flow                        | Wetted Material   | Stainless Steel                   |
| Capacity                     | 1 gpm (4 L/Min)                    | TMP Suction Range | 0-15 PSI (0-1 Bar)                |
| Operating Modes              | Demand Flow                        | Gasket Material   | Viton Or EPDM                     |
| Filtration Mode              | Outside In                         | NEC               | NFPA70, NFPA79<br>NFPA496, UL508A |
| Concentrate                  | 8lbs @ 20%                         | Remote            | Internet / WiFi                   |
| Application Engineering Data |                                    |                   |                                   |
| Power *                      | 480 Volt, 3Ø, 50/60Hz<br>3 FLA std | Inlet             | 5cm (1") 150# Flange              |
| Network                      | Profinet                           | Outlet            | 5cm (1") 150# Flange              |
| Instrument Air               | 1 cfm Oil Free<br>6 Bar (100 PSI)  | Air Supply        | 1.27cm (1/2") NPT                 |
| Weight Dry/Wet               | 225kg (550lbs)                     | Conveyor Outreach | Flapper                           |

\*May vary with each application



