



Nominal Capacity

0.2 MGD @ 250 GFD


0.8 MLD @ 425 LMH

4 Minutes from Raw to Filtrate Water

TYPICAL SYSTEM DETAILS			
Duty	>99%	Control	Fully Automated with Remote
Turndown	0-100% Automatic	Membrane Life	No End of Life
Filtrate Loss	0% ZLD	Wetted Material	Stainless Steel/FRP
Operating Modes	Continuous or On Demand	Certified	NSF/ANSI/CAN 61-372
Feed Modes	Pressurized or Gravity	Gasket Material	Viton or EPDM
Power	480 Volt, 60Hz 10 FLA	Electrical Codes	NFPA70, NFPA79 NFPA496, UL508A
Network	PROFINET	Inlet	4" 150# Flange
Instrument Air	Oil Free 120 PSI, 8 Bar	Outlet	4" 150# Flange No PVC
Weight Dry/Wet	8,000/27,500 LBS 3500/12500 KG	Concentrate/<i>SRU</i> Discharge	1" 150# Flange

Obtain equipment drawings for Application Engineering & Detailed Design.





OPTIONS			
Break Tank	Secondary Disinfection	DO Addition	Strainers / Screens
Inline pH Control	Level & Flow Control	Coagulant Feed	Turbidity Measurement
Inline Oxidation	Feed Pump & Drives	Camera	Direct Integrity Test
Chloride Resistant	-	ZLD	Solids Recovery

