



## Equipment Specifications \*

|                    |                   |                   |                                   |
|--------------------|-------------------|-------------------|-----------------------------------|
| Automatic Turndown | 0-100% Flow       | Wetted Material   | Stainless Steel                   |
| Nominal Capacity   | 70gpm (260 L/Min) | TMP Suction Range | 0-15 PSI(0-1 Bar)                 |
| Operating Modes    | Demand Flow       | Gasket Material   | Viton Or EPDM                     |
| Filtration Mode    | Outside In        | NEC               | NFPA70, NFPA79<br>NFPA496, UL508A |
| Solids*            | 500lbs/hr @ 20%   | Remote            | Internet / WiFi                   |

## Application Engineering Data

|                |                                     |                   |                            |
|----------------|-------------------------------------|-------------------|----------------------------|
| Power*         | 480 Volt, 3Ø, 50/60Hz<br>13 FLA std | Conveyor Outreach | 2' Standard<br>4' Optional |
| Network        | Profinet                            | Inlet             | 2" #150 Flange             |
| Instrument Air | 1 cfm Oil Free<br>100 PSI (6 Bar)   | Outlet            | 2" #150 Flange             |
| Weight Dry/Wet | 2,075 lbs (941 kg)                  | Air Supply        | 1/2" NPT                   |

\*May vary with each application



